

SITE PLAN CONTROL BY-LAW

THE CORPORATION OF THE CITY OF MISSISSAUGA

BY-LAW NO. 0293-2006

NOTE:

This is an "OFFICE CONSOLIDATION" of By-law No. 0293-2006, City of Mississauga Site Plan Control By-law, approved by City Council, July 05, 2006, and came into force and effect, July 05, 2006, and incorporates all amendments made to the said by-law.

For accurate reference the "ORIGINAL" of the individual by-laws should be consulted. Copies of "ORIGINAL" by-laws are available at the Office of the City Clerk, Corporate Services Department.

The number in brackets, i.e., (1234-2006), at the end of a section, subsection, clause or schedule, is the number of the by-law amending By-law No. 0293-2006 that implemented or amended that section, subsection, clause or schedule.

Not to be reproduced without permission Copyright © 2006 City of Mississauga

Date of updates to the "Office Consolidation" and latest By-law in force:						
Amending By-law No.	Amendment	Enacted and Passed	In Force			
0080-2007	Delete and replace subsection 5(n) Add schedule 10	February 28, 2007	February 28, 2007			
0162-2007	Amend subsection 5(a)	April 25, 2007	April 25, 2007			
0238-2007	Delete and replace subsections 4(c), (d), 5(a), (d), (e), (h), (m) Amend subsection 5(b) Add subsection 5(o)	June 20, 2007	June 20, 2007			
0359-2007	Add subsection 5(p)	September 26, 2007	September 26, 2007			
0146-2008	Add subsection 5(q) Add schedule 11	May 07, 2008	May 07, 2008			
0185-2010	Amend subsection 5(a) Delete and replace clause 5(m)(ii) and schedules 1, 2, 3, 7 and 7B	June 23, 2010	June 23, 2010			
0145-2012	Delete and replace subsection 5(a)	July 04, 2012	July 04, 2012			
0051-2013	Add clause 5(r)(i) Add schedules 12 and 12A	March 06, 2013	March 06, 2013			
0028-2014	Add subsections 5(s), (t) Amend schedules 4 and 5 Add schedule 5A	February 12, 2014	February 12, 2014			
0118-2014	Add subsection 5(u) Add schedules 13, 13A, 13B and 13C	May 14, 2014	May 14, 2014			
0247-2014	Add subsection 5(v) Add schedule 14	September 10, 2014	September 10, 2014			
0282-2014	Delete and replace subsection 5(c) Amend schedule 3	December 17, 2014	December 17, 2014			

Date of updates to the "Office Consolidation" and latest By-law in force:							
Amending By-law No.	Amendment	Enacted and Passed	In Force				
0030-2016	Delete and replace second preamble, subsection 5(a) and schedule 2 Delete subsections 5(n), (q) and schedules 10 and 11	February 24, 2016	February 24, 2016				
0204-2017	Delete subsection 4(d) and clause 5(m)(iv) Amend clause 5(m)(ii) Delete and replace schedules 7 and 7A	November 22, 2017	November 22, 2017				

SITE PLAN CONTROL BY-LAW

THE CORPORATION OF THE CITY OF MISSISSAUGA

BY-LAW NO. 0293-2006

A By-law to provide for Site Plan Control in the City of Mississauga and to repeal By-law 1127-85, as amended, and By-law 314-89.

WHEREAS section 41 of the *Planning Act,* R.S.O. 1990, c.P.13, as amended, permits the Council of a municipality to designate the whole or any part of the municipality as a Site Plan Control Area, where in the Official Plan the area is shown or described as a proposed Site Plan Control Area;

AND WHEREAS section 19.14.1 of the Official Plan for the City of Mississauga (Mississauga Official Plan) designates all lands in the City of Mississauga as a Site Plan Control Area; (0030-2016)

AND WHEREAS subsection 41(11) of the *Planning Act,* R.S.O. 1990, c.P.13, as amended, refers to section 427 of the *Municipal Act 2001,* S.O. 2001, c.25, as amended, which permits a municipality to direct or require that a matter or thing be done at the person's expense and may recover the costs by action of doing said thing or matter from the person directed or required to do it;

NOW THEREFORE the Council of the Corporation of the City of Mississauga ENACTS as follows:

- **1.** For the purposes of this By-law:
 - (a) "CITY" means the Corporation of the City of Mississauga;
 - (b) "COMMISSIONER" means the Commissioner of the Planning and Building Department, including his or her designate as identified by the Commissioner in writing from time to time;
 - (c) "COUNCIL" means the Council of The Corporation of the City of Mississauga;
 - (d) "DEVELOPMENT" has the same meaning as in subsection 41(1) of the *Planning Act*, R.S.O. 1990, c.P.13, as amended;
 - (e) "OWNER" means any owner of land as identified in the records of the proper Land Registry Office or Land Titles Office and includes a purchaser under a valid Agreement of Purchase and Sale, and the authorized agent of any such purchaser or owner of land;
 - (f) "REDEVELOPMENT" means the removal of buildings or structures from land and the construction or erection of other buildings or structures thereon and "REDEVELOP" has a corresponding meaning;
 - (g) "SITE PLAN" means those plans and/or drawings as contemplated by subsection 41(4) of the *Planning Act*, R.S.O. 1990, c.P.13., as amended;
 - (h) "SITE PLAN UNDERTAKING" means an agreement as contemplated by subsection 41(7)(c) of the *Planning Act*, R.S.O. 1990, c.P.13, as amended, regarding matters pertaining to the development or redevelopment of a property subject to site plan control, and which may appear in the form of a document called a Site Plan Undertaking or as a Site Plan Development Agreement, as approved by the Commissioner, and signed by both the owner and the Commissioner;
 - "SITE WORKS" means all of those requirements made by the Commissioner as identified on a site plan for land which is to be developed or redeveloped, drawn to a suitable scale and showing thereon the following:
 - the location, size and design of all matters provided for under subsections 41(4), (7) and (8) of the *Planning Act*, R.S.O. 1990, c.P.13, as amended;

- the dimensions and area of land and the boundary lines of all lots that comprise the land, certified by or taken from a drawing prepared by an Ontario Land Surveyor;
- (iii) buildings and structures which are to remain on the land and all setback measurements related thereto;
- (iv) landscaping works, including location, size and description of all hedges, trees, shrubs and other landscaping, and detailed tree replacement and tree planting information; and,
- such other data as may be required by the Commissioner consistent with the provisions of the *Planning Act*, R.S.O. 1990, c.P.13, as amended.
- 2. All the lands within the municipal boundaries of the City are hereby designated as a Site Plan Control Area, and no person shall undertake development on the lands without the approval of a site plan by Council.
- **3.** Council hereby delegates to the Commissioner the powers and authority conferred upon the Council under section 41 of the *Planning Act,* R.S.O. 1990, c.P.13, as amended, except the authority to define any class of or classes of development that may be undertaken without the approval of a site plan.
- 4. Section 2 of this By-law shall not apply to the following classes of development:
 - (a) Detached dwellings having direct frontage on a public road;
 - (b) Semi-detached dwellings having direct frontage on a public road;
 - (c) Lands with an Employment Zone; (0238-2007)
 - (d) (0238-2007), deleted by (0204-2017)
- **5.** Notwithstanding section 4 of this By-law, section 2 of this By-law shall apply to the following classes of development:
 - (a) All development and redevelopment on lands zoned "R1-29", "R1-47", "R3-14", "R9-1", "RM2-48", "RM2-54", "E3-15", "D-6", "D-7"; (0162-2007), (0238-2007), (0185-2010), (0145-2012), (0030-2016)
 - (b) All development or redevelopment on lands used for the office of a resident physician, dentist, drugless practitioner or health professional in a detached dwelling; (0238-2007)
 - (c) All development or redevelopment on the lands with the municipal addresses 1355 Aerowood Drive, 6865 Century Avenue and Block B, Registered Plan M-13; (0282-2014)
 - (d) All buildings and structures on lands zoned "U" (Utility) having a floor area greater than 10 m²; (0238-2007)
 - (e) All development or redevelopment on lands with an Employment Zone which abut the roads shown on Schedules "1" and "2" attached to this By-law; (0238-2007)
 - (f) All development or redevelopment on the lands shown on Schedule "3" attached to this By-law;
 - (g) All development or redevelopment on the lands shown on Schedule "4" attached to this By-law;
 - (h) All development or redevelopment on lands zoned for detached dwellings on the lands shown on Schedule "5" attached to this By-law; (0238-2007)
 - (i) All development or redevelopment on the lands shown on Schedule "6" attached to this By-law;

- (j) All development or redevelopment on the lands shown on Schedule "7" (lands fronting, flanking and/or abutting Mississauga Road), attached to this By-law;
- (k) All development or redevelopment on the lands shown on Schedule "8" (the Port Credit Heritage Conservation District) attached to this By-law;
- (I) All development or redevelopment on the lands shown on Schedule "9" attached to this By-law;
- (m) All development or redevelopment on lands zoned:
 - Employment which are within 60 m of lands zoned residential and not otherwise subject to site plan control through other sections of this By-law; (0238-2007)
 - Employment which abut or include lands zoned greenlands, open space, parkway belt and greenlands overlay; (0238-2007), (0185-2010), (0204-2017)
 - (iii) "D" (Development) which are used for a non-residential use; and, (0238-2007)
 - (iv) (0238-2007), deleted by (0204-2017)
- (n) deleted by (0030-2016)
- (o) All power generating facilities; (0238-2007)
- (p) All development or redevelopment of lands for a vehicle pound facility; (0359-2007)
- (q) deleted by (0030-2016)
- (r) All development or redevelopment on the lands shown on Schedule "12" attached to this By-law, subject to the following: (0051-2013)
 - (i) All applications for site plan approval made on lands as shown on Schedule "12" must provide such plans and drawings as required under Subsection 41(4) of the *Planning Act* which are consistent with the Built Form Standards, attached hereto as Schedule "12A";
- (s) All development or redevelopment of lands for a temporary sales trailer; (0028-2014)
- (t) All development or redevelopment of outdoor play areas accessory to a day care use, as licensed under the *Day Nurseries Act*, (0028-2014)
- (u) All development or redevelopment on the lands shown on Schedule "13" attached to this By-law; (0118-2014)
- (v) All development or redevelopment on the lands shown on Schedule "14" attached to this By-law. (0247-2014)
- 6. The Commissioner may require that securities be posted by the owner, in such amount as the Commissioner deems necessary and appropriate, to ensure the provision and maintenance of the site works as shown on an approved site plan. Securities are to be submitted in a form deemed acceptable to the Commissioner.
- 7. The Commissioner may require an owner to provide and execute a site plan undertaking to ensure compliance with the conditions to provide, maintain or complete the site works as required by the Commissioner.
- 8. If an owner is in default of carrying out site works by failing to comply with the conditions to provide, maintain or complete the site works as required by the Commissioner, then the City, its authorized agents, servants or employees may enter upon the owner's land or into the owner's structures with reasonable notice to complete the site works at the owner's expense.

- **9.** The City may recover any costs incurred by the City, including interest and administration expenses, to provide, maintain or complete site works by deducting from or drawing upon securities that have been provided to the City by the owner. If there are no securities, or if the amount of securities held by the City are not sufficient to cover the costs incurred by the City, then without limiting the City's remedies the costs incurred by the City which can not be reimbursed or recovered from securities will be added to the tax roll of the property that is the subject of the site works and will be collected in the same manner as taxes.
- **10.** The Commissioner is hereby delegated the authority to determine and direct the appropriate action to be taken in the administration of this By-law, including any remedial action to be taken where an owner defaults in the carrying out of the site works.
- **11.** Should a court of competent jurisdiction declare any section or part of a section of this By-law invalid, it is the stated intention of Council that the remainder of this By-law shall continue in force unless the court makes an order to the contrary.
- 12. (a) By-law 1127-85, and amending By-laws 171-86, 267-86, 996-86, 1042-86, 1099-86, 16-87, 865-87, 214-88, 66-89, 112-89, 191-89, 257-89, 268-89, 319-89, 437-89, 487-89, 543-89, 622-89, 100-90, 120-90, 188-90, 443-90, 489-90, 11-91, 24-91, 83-91, 188-91, 332-91, 464-91, 126-92, 311-92, 361-92, 462-92, 552-92, 554-92, 286-94, 370-95, 268-96, 401-96, 164-97, 533-97, 628-97, 630-97, 58-98, 410-98, 424-98, 512-98, 23-99, 54-99, 158-99, 363-99, 369-99, 479-99, 0095-2000, 0333-2000, 0349-2000, 0405-2000, 0492-2000, 0577-2000, 0584-2000, 0073-2001, 0183-2001, 0288-2001, 0314-2001, 0347-2001, 0406-2001, 0486-2001, 0504-2001, 0015-2002, 0452-2002, 0086-2003, 0364-2003, 0476-2003, 0229-2004, 0275-2004, 0338-2005, 0054-2006 are hereby repealed.
 - (b) By-law 314-89 is hereby repealed.

ENACTED and PASSED this 5th day of July 2006.

"HAZEL McCALLION"

MAYOR

"CRYSTAL GREER"

CLERK





























Schedule "10" to By-law 0293-2006 deleted by (0030-2016)

Schedule "11" to By-law 0293-2006 deleted by (0030-2016)



SCHEDULE 12A

DOWNTOWN CORE Built Form Standards

January 22, 2013





DOWNTOWN CORE BUILT FORM STANDARDS

TABLE OF CONTENTS

IN.	TRODU	CTION	-	
	1.0	Purpose of the Standards	3	
	2.0	Objectives of the Standards	3	
	3.0	Expectations of the Standards	4	
		3.1 How to Read the Standards	5	
тн	E FRON	TAGE STANDARDS		
	4.0	Downtown Core Street Frontages	6	
	5.0	General Standards for Buildings on 'A' and 'B' Street Frontages	8	
		5.1 Standards for Buildings on 'A' Street Frontages	10	
	-	5.2 Standards for Buildings on 'B' Street Frontages	12	
	1	5.3 Design for Access, Parking, Service and Loading ('B' Streets)	14	
	6.0	Buildings Facing Parks and Open Space	15	
	7.0	Ground Floor Treatments	16	
	1	7.1 General Standards for Retail Uses (All Streets)	16	
	-	7.2 Retail Activation Streets and Standards	20	
	8.0	Design for Structured Parking Facilities	22	
BU	ILDING	DESIGN STANDARDS		
	0.0	Minimum Ruilding Height	24	
	10.0	Streetwall and Building Facade Treatments	25	
	10.0			
TA	TALL BUILDING STANDARDS			
	11.0	Tall Buildings ~ Overview	27	
		11.1 Massing Standards	28	
		11.2 Podium Design	30	
		11.3 Middle Shaft (Residential Towers)	32	
		11.4 Uninterrupted Tower Shafts	33	
		11.5 Site Orientation	34	
		11.6 Park Orientation	34	
		11.7 Tower Top	35	
		11.8 Built Form Compatibility & Transition to Adjacent Development	36	
		11.9 Design for at grade Residential Uses	38	
GL	OSSAR	Υ	40	



1.0 Purpose of the Standards

The purpose of the Downtown Core Built Form Standards is to provide urban design direction and guidance for proposed development at the planning application stage in order to assess, promote and fulfill the intent of the City's official plan policies, Downtown21 vision and zoning bylaw - all of which shape and have influence on the urban structure, built form qualities and overall character of the Downtown Core.

Selected content from this document, has been incorporated into the Local Area Plan as Official Plan policy in addition to the zoning by-law. Applicants should also refer to the Mississauga Official Plan principal document (MOP), Downtown Core Local Area Plan, Zoning By-law, and Building Code to ensure that the applicable policies and requirements in these documents have been met. Furthermore, other City initiatives and special projects should be consulted to determine applicability, such as the Strategic Plan, Downtown21 Master Plan, Green Development Strategy, Hurontario Light Rail Transit Study, Accessibility Design Handbook and the City of Mississauga Standards for Shadow Studies, etc.

2.0 Objectives of the Standards

Chapter 9 of the MOP, 'Build a Desirable Urban Form' is a fundamental component of the Plan. This section along with the policies contained within Section 12 'Downtown' and the 'Downtown Local Area Plan' set out the urban design policies which support the vision for a vibrant Downtown Core. These built form standards act to articulate the policies in addition to the following objectives:

 Support the City of Mississauga's Strategic Plan and its Strategic Pillars for Change - a paramount goal is to *Create a Vibrant Downtown* that functions as a strong economic centre, while acting as the civic heart and soul of the city;

- Promote development that supports and implements the six guiding principles of the Downtown21 Master Plan; specifically, #6 -'Create a Development Framework with Predictability' which recommends creating a policy framework that directs downtown development in a coordinated, comprehensive fashion through new urban design standards;
- Facilitate the fair and consistent application of design objectives;
- Integrate a mix of uses, through appropriate built form, including retail and commercial uses, offices, residential, cultural, entertainment and institutional uses — the whole of which is intended to put people in close proximity to a broad range of urban amenities and experiences;
- Achieve a high quality built form and strengthen the continuity of buildings that contribute to the emerging Downtown Core urban context;
- Ensure that development is resilient, environmentally friendly, safe and universally accessible; and
- Foster compact, pedestrian and transit oriented development that achieves vibrant street level activity and a public realm of the highest standard.



The 20th Century was about getting around. The 21st Century will be about staying in a place worth staying in.

~ James Howard Kunstler



3.0 Expectation of the Standards

The Built Form Standards provide further direction on the Urban Design Policies set out in the Official Plan, Downtown21 Master Plan in addition to other city initiatives that support land use decisions and strategies for the Downtown Core.

The Standards set out detailed requirements to achieve a high quality built form in the Downtown Core that interfaces with the public realm in a seamless fashion. The Built Form Standards have been developed to communicate the design expectations, in advance of an application being filed, related to the quality and outcome of development.

The standards, in addition to the dimensions indicated, are to be addressed and achieved by development

proponents through the planning application process. Depending on the context or site, exceptions to the Standards may be considered at the discretion of the City, in whole or part, when there are extenuating site circumstances and/or where proposals are able demonstrate urban design excellence.

It should be noted that the standards may be amended, modified or updated on an as-needed basis to provide clarity on the intent of the Downtown21 Master Plan, the Downtown Core Local Area Plan, provisions of the Zoning By-law including the outcome of other studies or initiatives that bear on the Downtown Core.







3.1 How to Read the Standards

The rationale of the Downtown Core Built Form Standards is best understood by reviewing all sections, text and diagrams, including the policies cited within the City's Official Plan (Downtown Core Local Area Plan). The Built Form Standards reflect an integrated approach to the Downtown Core, in which buildings are keyed to the streets through street frontage standards that guide and provide direction on the general disposition of buildings through form-based design.

Moreover, the Standards are also contingent on an understanding that downtowns are complex urban places that require an overarching organizing structure with a view to creating a coherent, legible, high quality public realm and memorable sense of place.







DOWNTOWN CORE STREET FRONTAGE PLAN

Figure 1: The Downtown Core Street Frontage Plan designates the frontage type for all existing and new streets in the Downtown Core. There are two categories - 'A' & 'B' Street Frontages. Refer to Downtown Core Local Area Plan policies and schedule.

4.0 Downtown Core Street Frontages

The City of Mississauga's Downtown Core vision (Downtown21 Master Plan) proposes new public streets to augment the existing public and private street pattern, thereby creating a comprehensive and interconnected urban grid. This framework is shown in the Downtown Core Street Frontage Plan above (see Figure 1).

Categories of frontages differentiate the various streets in the Downtown Core according to their function, character and design. As such, all streets are categorized as 'A' and/or 'B' frontages. 'A' Street Frontages will require the highest attention to urban design, having a cohesive built form to achieve character and a vibrant pedestrian environment.

Similarly, 'B' Street Frontages are designed to ensure a quality pedestrian environment and high standard of built form, but provide defined locations for necessary access, delivery, service, loading and parking facilities serving development blocks.

In general, new development will follow specified standards for each street frontage type which prescribes how buildings (through their site design, streetwalls, built form treatments, etc.) individually contain and provide visual enclosure of the street or open space in order to collectively frame and animate the public realm.





Petrosino Square, Manhattan, NYC.

For each type of street frontage ('A' and/or 'B') the standards outline specific design requirements for new buildings such as:

- Building Location and Streetwall Placement
- Access, Loading and Servicing
- Buildings Facing Open Space
- Buildings Containing Structured Parking
- Ground Floor Treatments
- Priority Retail Activation Streets

- Minimum Building Height
- Treatments for Building Facades and Streetwalls
- Tall Buildings; and
- Transition to Adjacent Development

The following sections set out the standards to be achieved for buildings along the frontage types in accordance with the Downtown Core Local Area Plan policies and the Downtown Core Street Frontage Plan:



5.0 General Standards for Buildings on 'A' & 'B' Street Frontages

Buildings are the most pronounced element of the urban fabric and create the sense of place. Buildings in the Downtown Core will shape and articulate the streets and open spaces by forming edges and streetwalls to establish definition and enclosure. Collectively, they create the pedestrian environment, frame the public realm and establish the urban setting. Common standards for 'A' and 'B' Street Frontages set up the urban framework for all development blocks in the Downtown Core.

The following standards will apply:

- **G1** Locate build-to-line requirements (within build-to areas) on development blocks to inform the orientation and placement of buildings and streetwalls;
- **G2** Coordinate build-to lines with adjacent properties in order to create consistent edges and street walls along frontages;
- **G3** Locate buildings parallel to the street, with streetwalls placed at the build to line, to contain the street and provide enclosure;
- **G4** Ensure a variation in set backs along the building frontages to articulate façade emphasis at the build-to-line, in order to allow for visual interest, accommodate outdoor patios, recessed entries and landscaped areas (*for setback provisions, refer to Section 5.1 Specific Standards for 'A' Streets and Section 5.2 Specific Standards for 'B' Streets);*
- **G5** Buildings should incorporate active uses at grade, such as commercial and retail, to animate the public realm and pedestrian environment (*Also, refer to Section 7.0 Ground Floor Treatments*);





- **G6** Ground floor uses will incorporate transparent windows;
- G7 Locate main entrances flush with the public sidewalk;
- **G8** Ensure site designs relate to and interface with existing, proposed and future transit stops and facilities;
- **G9** Locate main building entrances so that they are clearly identifiable and prominent with direct access to the public sidewalk, pedestrian connections and transit facilities;
- **G10** Where appropriate, provide corner entrances to buildings located at prominent intersections and/or gateways;



- **G11** Balconies may not protrude into the public realm, but may extend as far as the build-to line;
- **G12** Below grade parking structures will not protrude into the public realm, but can extend as far as the property line provided that a clearance of 1.5 m is provided between the top of the parking structure slab and sidewalk.





5.1 Standards for Buildings on 'A' Street Frontages

'A' Street have a critical role and function in the Downtown Core. They are the most important for securing animation and character, a comfortable pedestrian environment with access to sunlight and sky views, street activity and vibrancy. Development fronting onto 'A' Streets will require the greatest attention to urban design, ensuring a cohesive built form and streetscape treatment to achieve the highest standard in the execution of the public realm.



The following standards will apply:

- A1 Provide continuous buildings along development blocks fronting onto 'A' Streets to provide continuity of built form from one property to the next;
- A2 A minimum of 90% of a property's frontage is required to be occupied by the streetwall at the build-to line;
- A3 Development will be prohibited from locating curb cuts, driveways and laneways on 'A' Streets;
- A4 A maximum of 25% (i.e. 25% of 90%) of the building frontage will be allowed to step back to a maximum of 4.5 m from the build-to line to allow for articulation of the streetwall, including provision for outdoor patios, recessed entries and landscaped areas;

- A5 Functioning main entrances to buildings will be provided on 'A' Streets. *(Also, see Section 7.0 Ground Floor Treatment);*
- A6 Ground floor elevations along 'A' frontages will have a minimum of 75% transparent vision glazing with views into the building; and
- A7 Where residential uses are permitted at the ground level, special provisions will apply for the design of unit entrances and setbacks (see Section 11.9 Design for at grade Residential Uses).

E-A3 Exceptions to Access on 'A' Streets:

Curb cuts, driveways and access may be provided on 'A'-Street frontages provided that:

- a site or block does not have access from a 'B' Street or other means of access, or if there is a requirement for emergency vehicle access; and
- impacts on the pedestrian environment are minimized through a high standard of design treatment consistent with the quality of the public realm.



required along the length of a property with provision for articulation and step-back of the streetwall.







Figure 11: Articulation of the façade along the buildto line provides visual interest at the street



Figure 12: Variation and step backs along the street wall provide visual interest.



MISSISSauga

5.2 Standards for Buildings on 'B' Street Frontages

'B' Streets generally connect 'A' Streets to each other. In contrast to 'A' Streets, they provide development blocks with access for deliveries, garbage pick-up, service and loading, including vehicular access to structured and off-street parking within development sites. It should be noted that 'B' Streets are also intended to support a pedestrian environment, integrating a high standard of urban design to support street activity.



The following standards will apply:

- **B1** 'B' Streets will have buildings along development blocks, with provision for vehicular access to off street parking, access for deliveries, garbage pick-up, servicing and loading (*refer to Section 5.3 Design for Access, Parking, Service and Loading*);
- **B2** A minimum of 75% of a property's frontage is required to be occupied by the streetwall at the build-to line;
- **B3** A maximum of 15% (i.e. 15% of 75%) of the building frontage will be allowed to step back to a maximum of 3.0 m from the build-to line, to allow for articulation of the streetwall, including provision for outdoor patios, recessed entries and landscaped areas;

- **B4** Provide functioning main entrances to buildings on 'B' Street frontages; and
- **B5** Ground floor elevations along 'B' frontages will have a minimum of 50% transparent vision glazing with views into the building.

E-B4 Exceptions to Access on 'B' Streets:

Where a development block has an 'A' and 'B' frontage, the most prominent building entrance will be located on the 'A' Street frontage.



Figure 15: Access to parking and services is discretely provided within these developments near the street edge, acknowledging the importance of the pedestrian realm.






Figure 17: 'B' frontages in the Downtown Core allow for service , loading and access, but are also envisioned to be pedestrian oriented with an attractive character.



Figure 18: Access to below grade parking is discretely executed at grade without compromise to the pedestrian environment or manner in which the building relates to the street.



Frontage Standards.



5.3 Design for Access, Parking, Service and Loading ('B' Streets)

Access for loading, garbage, parking and servicing to buildings will be located on 'B' Streets *(for exceptions, refer to Section 5.1, 'Standards for Buildings on 'A' Frontages'*). In general, new development will coordinate the location of service areas for delivery, parking, loading and garbage pick-up and will reduce vehicular interruptions along the public street in order to improve the aesthetic appeal of the streetscape.

The following standards will apply:

- **SL1** Service, parking and loading should be coordinated on sites by providing consolidated locations that can serve a number of buildings simultaneously from one area;
- **SL2** Loading, garbage and service spaces will be located internal to the building to avoid noise and visual impacts;
- **SL3** Loading, servicing, other vehicular related functions and utilities will not detract from the use, safety or attractiveness of the pedestrian and public realm by:
 - incorporating special architectural treatment;
 - using soft and hard landscape treatments to screen loading and servicing areas; and
 - providing safe levels of illumination and lighting.
- **SL4** The height required for overhead loading for bulk refuse within a collection area should conform to the Region on Peel's standards for overhead clearance;



Figure 20: Above / Below -Vehicular access for loading, servicing and parking is designed in a compact fashion and integrated with the building façade.





14

6.0 Buildings Facing Parks and Open Space

New buildings which front onto, or have proximity to parks and open space will require special attention to their frontage treatments and architectural design in order to achieve the kind of character, sense of place and pedestrian experience warranted for these important elements of the public realm.

The following standards will apply:

- **OS1** If the build-to line of a development fronts onto the edge, or street adjoining a public park or open space, then 'A' frontage requirements will apply (*refer to Section 5.1 'Standards for Buildings on 'A' Frontages'*);
- **OS2** Building frontages along parks and open spaces will have uses on the ground floor to animate and/or activate the frontage such as retail, commercial and/or residential uses;
- **OS3** Buildings which surround, have proximity, or front -onto parks and open space will have the highest level of architectural expression, articulation and use of materials;
- **OS4** At grade level residential uses fronting onto parks and open space will have individual unit entrances in order to animate the street environment (*refer to Section 11.9 Design for At* grade Residential Uses);
- **OS5** Parking structures or surface parking lots will not be permitted to front onto or address parks and open spaces; and
- **OS6** The design of building massing will protect for maximum sun exposure onto parks and open space. (*Refer to Section 11.5 & 11.6 Tall Buildings 'Site / Park Orientation').*







7.0 Ground Floor Treatments

7.1 General Standards for Retail Uses (All Streets)

To ensure well designed ground floors, at-grade conditions incorporating retail uses must be carefully executed in order to animate the street edge and support the pedestrian experience. The following standards will apply to all streets in the Downtown Core (inclusive of those identified in Section 7.1 Retail Activation Streets):

- **GF1** Ground floor heights will be a minimum of 4.5 metres (floor-to-floor, measured from established grade) to accommodate retail and commercial uses with windows that correspond to the height of ground floors;
- **GF2** The primary entrance to each street-level tenant space that has its frontage along a public street will be provided from that street;
- **GF3** Where retail units occupy prominent corner locations, design units to:
 - address the corner with well designed, animated storefronts that wrap the corner; and
 - incorporate corner entrances;
- **GF4** Entrances to retail and commercial tenant spaces will be operational, flush and directly related to the grade of the public sidewalk;



- **GF5** Entrance doors to retail units should be recessed within storefronts in order to minimize conflicts between door swings and pedestrians;
- **GF6** Ensure that ground floors containing storefronts articulate:
 - a strong sense of rhythm and pattern collectively across frontages;
 - subtle recesses and reveals to create depth and visual interest; and
 - assist pedestrians with spatial perception, orientation and accessibility along retail frontages.



16





- **GF7** At grade retail and commercial uses will incorporate the highest standard of storefront design consisting of:
 - Durable, high quality materials such as wood, metal (steel and anodized aluminium, etc), glass, natural stone and brick;
 - Clear transparent windows and doors that allow for views into and out of storefronts;
 - Dark tinted, reflective or opaque glazing or 'appliqué lifestyle' panels placed on storefront windows are not permitted in the Downtown Core; and
 - Elements such as mullions, glazing bars and transoms to help frame, divide and define storefront window sections and apertures;
- **GF8** When part of a larger single development or individual tenancy, provide coordinated and consistent signage and lighting that integrates with the storefront design, and which compliments or acts as an extension of the buildings architectural character;
- **GF9** The incorporation of architectural cantilevers, fixed canopies, awnings or similar features into a proposed development will be provided in order to achieve pedestrian scale, comfort and weather sheltered pedestrian routes. These should compliment the architectural character of the building and be made of highly durable materials, extending a min. of 1.5 m to a max. of 2.75 m, protrusion beyond the retail edge and/or into the public sidewalk area (refer to Figure 25); however, such installations should not conflict or interfere with any streetscaping elements or public realm treatments;
- **GF10** Where appropriate, patios and outdoor amenity space should be provided adjacent to retail/ commercial frontages or entrances to promote activation of the street and vibrancy; and
- **GF11** Patios should have a depth of at least 2.5 m. and can be recessed into the building as part of the permitted setback from the build-to line, or placed beyond the build-to line along the spillout zone providing that there is sufficient space. A clear sidewalk width is required to ensure pedestrian traffic flow is not disrupted.



General Standards for Ground Floor Treatments

DESIGN for STOREFRONTS

Buildings incorporating at grade commercial and/or retail uses will be designed to ensure that such uses will be directly related to the public sidewalk and will incorporate operating entrances, doorways and storefront windows oriented to the street; along with signage and lighting to provide animation, interest and variety in the streetscape.





General Standards for Ground Floor Treatments

DESIGN for OUTSIDE PATIO AREAS & PEDESTRIAN COMFORT



Patios can be recessed into the building as part of the permitted setback at the build-to frontage, or placed beyond the build-to line along the 'shy zone' providing that there is sufficient space and where pedestrian traffic flow is not disrupted.





Developments will incorporate architectural cantilevers, fixed canopies, awnings or similar features in order to achieve pedestrian scale, comfort and weather sheltered pedestrian routes. These should complement the architectural character of the building and be made of highly durable materials. Patios and amenity space should be provided adjacent to retail /commercial entrances to promote activation and street vibrancy.



Figure 25: Design elements such as awnings and patios extend from storefronts to activate the street and create the urban experience for pedestrians.





Downtown Core Retail Activation Street Plan



Figure 26: The Retail Activation Plan identifies retail objectives in the Downtown Core for existing and new streets. Also, refer to Downtown Core Local Area Plan - Retail Activation Policies and Schedule.

7.2 Retail Activation Street Standards

Existing and new streets in the Downtown Core have been identified for the purpose of establishing retail objectives within mixed use buildings. The Retail Activation Plan (shown above) identifies districts and areas of focus for which retail has been determined to be a strategic priority, setting out requirements for the amount of at-grade retail to be achieved on ground floors (corresponding to 75% or 50% minimum requirements).

In addition to the standards outlined in Section 7.0 'Ground Floor Treatments for At-grade Retail Uses', the design of units fronting onto Retail Activation Streets in the Downtown Core will:

- **RA1** Provide narrow storefronts to a maximum unit width of 10 m;
- RA2 Have a minimum unit depth of 10 m;

- **RA3** Design the entrances to retail units to a maximum spacing of 10 m between successive storefronts; and
- **RA4** To ensure the integrity of retail activation streets, main front entrances and lobbies that serve residential uses above the ground storey will be:
 - limited to a maximum width of 6.5 m.;
 - located to establish and reinforce patterns of access between blocks of development; and
 - positioned so that there is minimal interruption of retail units along the block.













8.0 Design for Structured Parking Facilities on 'A' and 'B' Street Frontages.

Parking facilities will have an important role to play in supporting key uses, attractions and urban amenities in the Downtown Core. In general, development will locate structured parking and vehicular access to minimize impacts on the property and on surrounding properties and to improve the safety and attractiveness of adjacent streets, parks and open spaces.

The following standards will apply:

- P1 Parking structures will not directly front onto 'A' Streets, but will be entirely screened by 'liner' buildings incorporating a mix of uses between the parking structure and street space in accordance with Section 5.0 – 5.1 for 'A' Street Frontages;
- P2 Liner uses should have a minimum depth of 10 m.;
- **P3** On the ground floor, parking structures will have active uses such as commercial or retail services with an appropriate scale and architectural expression to support activity on the streets, including those fronting onto parks and/or open spaces (*refer to Section 7.0 . Ground Floor Treatments*);
- P4 Parking structures will only directly front onto one 'B' Street where more than one 'B' street frontage exists;
- **P5** When fronting onto 'B' Streets, parking structure façade elevations will be designed to the highest level of architectural treatment and animation to mask the parking and screen views of the interior;
- **P6** Entrances, lobbies and passageways that provide a convenient means of access to parking facilities will be fully enclosed, appropriately signed and integrated into the façade design without appearing as dominant elements on the street frontages;

- **P7** At grade exhaust vents serving structured parking facilities will be:
 - located to minimize negative impacts on the public realm; and
 - integrated into the design of buildings, expressed as part of the architectural character.
- **P8** Consult the PEEL CPTED (Crime Prevention Through Environmental Design) Guidelines for the Design of Parking Garages.









Figure 30: Facades that are articulated with architectural treatment to resemble authentic buildings, and/or more animated approaches are used to mask structured parking (applicable to 'B' Streets).



Figure 31: A typical condition for a 'B' frontage in which at grade retail is incorporated at the base and the structured parking above is enclosed by façade treatments to screen the stalls and interior parking areas.



9.0 Minimum Building Height

Mississauga's vision to urbanize the Downtown Core is intended to provide, a compact, mixed-use urban form that puts people in close proximity to jobs, transit, and a broad range of uses and urban amenities. To achieve this, a minimum building height of three storeys needs to be deployed to ensure the most efficient use of land and to create a pedestrian environment through street walls that contain the street and supports transit. In a downtown environment, one-storey temporary format buildings, such as big-box retail or entertainment facilities, served by surface parking, are examples of building typologies which are inefficient, suburban and do not lend themselves to creating a pedestrian friendly environment.



The following standards will apply:

BH1 All new buildings in the Downtown Core must achieve a minimum height of 10.7 metres (3 Storeys) both at the street frontage and across the entire area of the building.

N.B. Applicants should also refer to 'A' and 'B' frontage standards concerning build-to requirements, building placement, step-backs, etc.





Figure 33: A 3 Storey mixed-use building with active ground floor retail/commercial uses contains the street and provides a comfortable pedestrian scale.





10.0 Streetwall and Building Façade Treatments

To ensure that development in the Downtown Core provides a strong sense of urbanity, the following built-form treatments will be incorporated into the design of buildings:

- **BF1** Mitigate the perception of large buildings and long frontages by:
 - ensuring buildings and their streetwalls are well proportioned to address human scale;
 - incorporating variation or special massing; and
 - providing a change in materials, textures, patterns, colours and details on building frontages to create a sense of smaller scale buildings;
- **BF2** Ensure that the design of streetwalls in mixed-use buildings deploy:
 - Base to strongly define the at grade level;
 - Middle to define the upper storeys; and
 - to express the termination of the streetwall at the roof-line, parapet, related floor juncture or storey, in a way that articulates the expression and character of the building;
 - Elements that accentuate floor and/or ceiling junctures and transitions between subsequent storeys. The should include horizontal expression lines, such as belt-courses, cornices, banding(s) or architectural treatments integrated into the streetwall expression;
- **BF3** Establish a rhythm, with frequency and articulation, across the streetwall by deploying elements that are vertically oriented and scaled to the pedestrian to include:
 - all forms of fenestration, including transparent windows, apertures, bow, bay, storefronts, dormer and monitor-style windows; and
 - pilasters, engaged columns, recesses, reveals, expression lines or other architectural treatments to create interest for the pedestrian and which serve to break up elongated facades.
- **BF4** Consider incorporating a balance in the proportion of glazing to solid wall materials in the design of facades in order to achieve pleasing symmetries and legible asymmetries;



- **BF5** Design corner lot buildings with special massing and architectural treatments on both streets to give prominence along the frontages and visually distinguish these sites;
- **BF6** Express principal building entrances with a height, proportion and level of articulation that is compatible with the ground floor storey height, so that entrances are visible and serve as focal points for orientation and access from the street (*also, see Section* 5.0 5.2, 'A'/'B' Standards for Street Frontage);
- **BF7** Incorporate upgraded doors for entrances, including egress and fire exit doors fronting onto streets;
- **BF8** Design balconies to be recessed and/or architecturally integrated into the design of the building façade incorporating high quality materials, balustrades and railings;
- **BF9** Integrate, conceal and screen roof top equipment into the complete building design;
- **BF10** Deploy a hierarchy of materials with solid, or 'heavier' materials located closer to the ground as a means to visually anchor the building to grade;





- **BF11** Construct building exteriors from enduring, natural materials such as clay brick, stone, metal, glass and wood in order to create durable buildings;
- **BF12** Building materials such as stucco, metal siding, embossed face brick panels, vinyl, and EIFS (Exterior Insulation Finish Systems) are not to be used in the Downtown Core;
- **BF13** Consider using building materials that are energy efficient and/or those that have been re-used or recycled (*Please consult the City of Mississauga's Green Development Standards for sustainable approaches and further direction*);
- **BF14** Building signage will be visually integrated with the development as sign-bands or fascia signs, and as an extension of the building's architectural expression;
- **BF15** Except for wayfinding signage and commemorative plaques, pylon and standalone signs are not permitted in the Downtown Core; and
- **BF16** Ensure that utilities, meters, gas pipes and other building services installed on the ground plane do not negatively impact the presentation or scenic quality of existing or proposed development in the Downtown Core.



TALL BUILDING STANDARDS



11.0 Tall Buildings ~ Overview

Tall buildings characterize a good part of the Downtown Core and have a role to play among other building types and land uses in the emerging downtown context.

Tall buildings are accompanied with significant civic obligations and responsibilities compared to other structures in the built environment. Spatially, they articulate the city pattern and urban structure, while visually reinforcing the civic importance of the Downtown Core and the image of the City as a whole.

Tall buildings must consider location, placement, relationship to the street, height ranges, built form qualities, architectural treatment and their ability to enhance the pedestrian environment by minimizing shadowing of the public realm. They need to protect important views, impacts on cultural resources and be able to accommodate a range of uses and support for transit. Tall buildings must also ensure that fundamental quality of life aspects are provided for, such as access to natural light, sky views and privacy for those that live, work and visit the Downtown Core.



11.1 **Massing Standards**

Tall buildings in the Downtown Core will be designed to consist of three parts:

Podium

The Podium will enclose and provide definition and appropriate scale for adjacent streets, parks and open spaces, and integrate with adjacent buildings and address the impacts of parking, loading and servicing uses.

The Podium includes the street level to midrise portion of the development which includes the streetwall. The Podium will be designed in accordance with the frontage and massing standards set out in this document.

Middle Shaft (Tower)

The floor plate size and shape of the middle shaft (tower) will be designed with appropriate dimensions for the site; the middle shaft will be located and oriented on the site and in relationship to the Podium and adjacent buildings.

Towers above the Podium height are governed by the massing standards which provide direction on slenderness, orientation and separation.

Тор

Design the top of the tall building to contribute to the skyline character and integrate roof top mechanical systems into the design.



Figure 36: The tripartite form of the Tall Building is well articulated in this Downtown Mississauga Development.





11.2 Podium Design

The design and placement of the podium requires careful consideration in terms of its role in helping to contain the street and achieving pedestrian scale qualities. Podiums will need to consider appropriate height in relation to the street right of way, streetwalls, and step-backs at the upper storeys, including ways in which sunlight can reach sidewalks to support a light-filled, vibrant public realm.

The following standards will apply:

- **T1** The podium height will generally be equal to the width of the right-of-way, but not less than 3 storeys (*refer to Figure 37*);
- **T2** The design of Podiums that front onto Burnamthorpe Road should:
 - not be less than 6 storeys in height; and
 - have a height that is compatible with the podiums of adjacent development (existing or proposed and where they exceed 6 storeys) subject to Standard 'T5';
- **T3** To support a pedestrian scale and contain the street, Podiums will also incorporate a street wall placed at the build-to-line, having a minimum of 3 storeys to a maximum of 5 storeys in height.
- **T4** Where right-of-ways exceed 60 m, the street wall can be increased to a maximum of 6 storeys in accordance with Standard `T2' (refer to Figure 38 and 39);
- **T5** Podiums and their street walls will be articulated and massed at the upper storeys using step-backs to:
 - mitigate the perception of height and create a comfortable scale for pedestrians;
 - maximize sunlight on the public realm in accordance with the parameters set out in the *City of Mississauga's Standards for Shadow Studies;*
 - mitigate the effects of wind on the pedestrian environment.

- **T6** Step backs of 3.0 m will be applied to the street wall and podium design in order to achieve the angular plane (Refer to City of Mississauga Standards for Shadow Studies);
- **T7** Towers should be set back a minimum of 3.0 m from the top tier of the Podium edge in order to establish a clear definition between the podium and tower (*Refer to Figure 39 for illustration of Podium Design*).
- **T8** When Tall Building proposals are phased, ensure that party walls of Podiums are architecturally treated and enhanced to address interim conditions.







for pedestrians using step backs to maximize sunlight on the public realm in accordance with the *City of Mississauga's Standards for Shadow Studies.*

<image>

Figure 40: Podiums when well designed and executed contribute positively to the pedestrian environment.



11.3 Middle Shaft (Residential Point Towers)

Compact slim towers and small floor plates minimize shadowing, maximize separation, and views between buildings. They also improve privacy and reduce overlook impacts on adjacent streets, parks, open spaces and properties.

The following standards will apply:

- **T9** Design and articulate the floor plates to break down the mass of the building and to create 'street interest' and enhance skyline character;
- **T10** Residential tower floor plates above the podium height will not exceed a maximum area of 850 m2 (gross, inclusive of internal elevator cores, servicing and circulation components) and should be designed to achieve proportionately slender tower profiles based on the suggested guideline:
 - 0 30 Storeys = 750 m2 (gross)
 - 0 40 Storeys = Up to 800 m2 (gross)
 - 0 50+ Storeys = Up to 850 m2 (gross)
- **T11** Provide a minimum spatial separation of 30 m between towers to maximize access to sky views, natural daylighting, adequate privacy, minimize wind conditions and collective shade on the streets, parks and open spaces;





Figure 41: Slenderness & Floor Plate — Compact slim towers with small floor plates minimize shadowing, maximize separation and views between buildings, and reduce privacy and overlook impacts. To achieve the objective of compact slimmer towers, yet allow for tower massing flexibility, floor plates above the podium will be designed to a maximum of 850 m2 (gross). See 'T9'.



Figure 42: **Tower Separation** — Spacing towers with minimum separation will minimize collective shade and sunlight impacts of closely-spaced towers on streets, parks and adjacent residential buildings. This will also achieve increased access to sky views and natural lighting as well as increased privacy. The minimum spacing between point towers will be a minimum of 30m.





11.4 Uninterrupted Tower Shafts

To allow for different tower expressions and juxtaposition of form in the Downtown Core, a portion of the tower shaft may vertically extend down to grade in order to allow for an uninterrupted tower expression when incorporated into a podium or larger development scheme, subject to the following:

- **T12** A maximum of 20% of the principle tower face may extend to grade without interruption by a Podium. Refer to Figure 40 for calculation of maximum allowable area of Uninterrupted Tower Shaft;
- **T13** The placement of the tower should not overshadow and impact sunlight on the public sidewalk;
- **T14** The setback to accommodate an uninterrupted tower shaft will count towards the allowable setback set out by the frontage standards for 'A' and 'B' Streets (*see Section 5.1—5.2, Street Frontage*);
- **T15** When deployed at corner locations, the exposed at grade portion of the tower will be designed to create a highly animated and active condition, with entrances, in order to positively reinforce and celebrate the corner;
- **T16** Tall building proposals must demonstrate that uninterrupted tower treatments do not introduce significant wind impacts on the pedestrian realm by virtue of the tower location itself;
- **T17** Introducing design elements at-grade to mitigate the effects of wind that are integrated with the architecture of the building or landscape design.





TALL BUILDING STANDARDS (cont'd)



11.5 Site Orientation

Point towers should be located on their sites to minimize shadow impacts on adjacent streets and open space. The following standards apply:

- **T18** Point towers should be located on the northwest and south-west sides of a block or development site so that shadows fall primarily within the block itself rather than on the street;
- **T19** Elongated floor plates should be oriented in a manner which minimizes shadow impacts this should be demonstrated in accordance with any sun/shadow studies that are required by the City;



11.6 Park Orientation

- **T20** Locate towers to minimize shadow impacts on adjacent parks and open spaces;
- **T21** For blocks on the southeast and southwest sides of a park, towers should be located on the farthest side of the block from the park;
- **T22** For blocks on the northeast and northwest sides of a park, point towers should be located on the southeast and southwest sides of the block;
- **T23** Buildings abutting or facing onto parks and open spaces will establish a maximum podium height and point tower location/massing that maximizes opportunities for sunlight exposure in accordance with the *City of Mississauga's Standards for Shadow Studies;*







11.7 Tower (Roof) Top

Towers contribute to the image of the Downtown Core. The tops of towers should be designed as distinctive elements against the skyline, when seen from the street or from a distance. Moreover, a welldesigned roofline creates opportunities for views to distinctive landmarks, including orientation and wayfinding.

- **T24** Design the uppermost floors of the tops of tall buildings to achieve a sculptural or distinctive profile;
- **T25** Design the tops of tall buildings to integrate and screen the mechanical penthouse function and other roof top units into the complete building design;
- **T26** Use materials, finishes and patterns that are consistent with the overall building design and architectural expression;
- **T27** Incorporate ways in which the roof top expression can be subtlety illuminated and enhanced with architectural lighting effects during evening hours;



11.8 Built Form Compatibility & Transition to Adjacent Development

Taller buildings should be sited and organized to provide a desirable transition to adjacent lower form buildings and open space. They should also ensure compatible relationships between buildings of differing scale through adequate spatial separation.

Where a significant difference in scale exists between building heights, development will be required to deploy transition strategies through massing and built form, to achieve a harmonious relationship between proposed and existing development, and/or adjacent open spaces.

The following standards will apply:

- **T28** Consider the size of the development area and the planned intensity of the use;
- **T29** Consider the context of adjacent low scale development and other aspects such as the street width or adjacent open space;
- **T30** Where a proposed development incorporates multiple buildings, design the buildings to step down in height from high to low, and where it abuts lower scale development;

- **T31** For large properties, use an angular plane of 45 degrees from the closest property line of lower scaled residential development, or open space, to determine the minimum setback and height of a building within a development;
- **T32** For single properties, deploy a stepping down of the building height and mass to achieve a transition to adjacent lower scale development or open space;
- **T33** Design the development to address the impacts of shadow, sky-views and how sunlight can be maximized on the private and public realm;
- **T34** Where a group of buildings and/or spaces act collectively to create a special architectural context (i.e. related by similar scale, heights, materials, colours, architectural character, landscaping and open space patterns or qualities) ensure that proposed infill development respects the context by deploying a strategy for building height that is compatible, and which positively contributes to the existing and/or anticipated pattern of development;
- **T35** Tall building proposals will not compromise important view corridors or silhouettes associated with the Mississauga Civic Centre/City Hall;









Figure 47: A progression in building heights over large blocks and areas can achieve more orderly arrangements and patterns in the built environment. Heights can be used to articulate and define the highest and most intense use of land, to the least intensive of uses.





11.9 **Design for At Grade Residential** (Horizontal Multiple Units)

Tall building proposals can integrate townhouse-form (horizontal multiple units) buildings to define edges, open space, streets and mews.

The following standards apply to townhouse form portions associated with tall buildings:

- **T36** Create a high quality interface and transition between the public sidewalk and front door to ensure adequate separation, definition and privacy; (refer to RT5 and RT6)
- Provide high quality landscape and treatments **T37** within frontages, transition zones and setbacks;
- **T38** Provide functioning, individual entrances to residential units and animate the frontage with windows on the ground floor that look out onto the street or open space; and
- Incorporate ways in which ground floor resi-**T39** dential uses may transition to commercial uses in the future;



Figure 48: Above - Townhouse units address

the street and incorporate landscaped transition areas between private individual entrances and the public sidewalk.



transition zones.



T40 Standard Design for Raised Residential Units

- Provide individual unit entrances from the sidewalk;
- Incorporate a minimum setback of 3.0 metres, which includes front steps (maximum 6 risers) and porch;
- Buffer to include architectural and landscape treatments such as a raised planter, low fencing or landscaping to augment the transition zone; and
- The ground floor should be raised between 0.9 1.2 metres above the sidewalk level;



T41 Standard for Grade Related Residential Units

(Including Retail Conversion as a Potential Future Use)

- Provide individual unit entrances that are grade related, with a direct connection to the public sidewalk;
- Incorporate a minimum setback of 4.5 metres;
- Buffer to include architectural and landscape treatments such as a raised planter, low fencing or landscaping to augment the transition zone; and
- Incorporate a minimum floor-to-floor height (ground floor to second floor) of 4.5 metres.

N.B. The City of Mississauga recognizes that there may be other approaches which achieve similar objectives for the conversion of at grade residential development to commercial/ retail uses. These will be will be considered and assessed for their merit at the application stages.





Articulation - architectural detail that refines and gives a building interest and added richness.

At grade - refers to the uses located at the ground storey, and generally the manner in which they are expressed or articulated to positively support the public realm.

Build-to-line – a designated line placed within the build-to area on a development block which informs the placement and orientation of the streetwall or building.

Built form - buildings and structures.

Compatible/Compatibility - when the density, form, bulk, massing, height, setbacks and/or materials of buildings are able to co-exist in harmony with their surroundings.

Curb cut - a break in the curb for vehicular access from the street onto a property.

Façade - means one or more exterior sides of a building, which may front onto or face a public space such as a street, park, access, etc.

Frontage Design - Refers to the built form urban design requirements associated with a category of frontage such as 'A' or 'B' frontage.

Glazing - clear or transparent glass windows whose physical attribute allows light to pass through completely. In reference to at grade uses, it enables views towards the inside of a building space from the exterior at the sidewalk level.

Liner Building - A liner building vertically places useable building space between a parking structure and the street space (build-to-line) in order to screen the parking from view.

Patio - an outdoor space generally used for dining that adjoins a restaurant, grocery store, coffee shop or café.

Pedestrian scale - a size of building, or space that a pedestrian perceives as not dominating or overpowering.

Main Building Entrance - The primary means of access which serves pedestrians, patrons and/or users of a building through a common entrance, internal lobby or vestibule that provides access to uses other than retail or commercial uses that are located at grade.

Podium - means the base of the building, structure or part thereof, located at or above established grade that project from the tower portion of the building.

Public realm - the streets, parks and open spaces that are available for any member of the public to access, use and enjoy.

Scale - the size of a building or an architectural feature in relation to its surroundings and to the size of a person.

Sidewalk - unobstructed pedestrian travel route generally situated with in the public right-of-way.

Spill-Out Zone - a space adjacent to storefront entrances where internal uses can spill out onto the public sidewalk or boulevard.

Streetscape - means the character of the street, including the street right-of-way, adjacent properties between the street right-of-way and building faces. Thus, the creation of a streetscape is achieved by the development of both public and private lands and may include planting, furniture, paving, etc.

Street frontage - the front and/or side of a property that faces an 'A' or 'B' street.

Streetwall – The façade of the building that defines the enclosure of the public space or street. It is defined through the use of a required step back at the upper storeys that articulates the building massing and establishes a consistent architectural line along the street frontage.

Step back – A required articulation of the building massing that helps establish the streetwall; it serves to reduce the appearance and bulk of the podium, mitigate the perception of height from the street and reduce shadow and wind impacts.

Storefront - the front of a store, or a room at the ground floor of a building that contains a display window at its front designed for commercial and retail uses.

Transit-supportive land uses - land uses that encourage transit use and transportation network efficiency.

N.B. Definitions in the Zoning By-law should be consulted and will take precedence over this Glossary.



DOWNTOWN CORE BUILT FORM STANDARDS

NOTES



DOWNTOWN CORE

Built Form Standards

Development and Design Division, Planning and Building Department

300 City Centre Drive, 6th Floor, Mississauga, ON L5B 3C1 Tel: 905-896-5511 Fax: 905-896-5553











